

## PLEXIGLAS® G-UVT ACRYLIC SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Company

Arkema Inc.  
2000 Market Street  
Philadelphia, Pennsylvania 19103

Altuglas International

**Customer Service Telephone Number:** (800) 523-1532  
(Monday through Friday, 8:30 AM to 5:30 PM EST)

#### Emergency Information

**Transportation:** CHEMTREC: (800) 424-9300  
(24 hrs., 7 days a week)

**Medical:** Rocky Mountain Poison Center: (303) 623-5716  
(24 hrs., 7 days a week)

#### Product Information

**Product name:** PLEXIGLAS® G-UVT ACRYLIC SHEET

**Synonyms:** Not available

**Molecular formula:** Not available

**Chemical family:** acrylic copolymer

**Product use:** Special applications, in general

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

**Color:** clear

**Physical state:** solid

**Form:** sheets

**Odor:** odourless

**CAUTION!**  
**PROCESSING MAY RELEASE VAPORS AND/OR FUMES WHICH CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.**

#### Potential Health Effects

**Primary routes of exposure:**  
Inhalation and skin contact.

**Signs and symptoms of acute exposure:**  
High molecular weight polymer. The product, in the form supplied, is not anticipated to produce significant adverse human health effects. Product dust may be irritating to eyes, skin and respiratory system. Effects due to processing releases: Irritating to eyes, respiratory system and skin. Inhalation of fume may cause flu-like symptoms. (severity of effects depends on extent of exposure) Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness.

**Remarks:**

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

Handle in accordance with good industrial hygiene and safety practice. (sheets) Secondary operations, such as grinding, sanding or sawing, can produce dust which may present a respiratory hazard. This product may release fume and/or vapor of variable composition depending on processing time and temperature.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name                      | CAS-No.      | Wt/Wt      | OSHA Hazardous |
|------------------------------------|--------------|------------|----------------|
| Polymethyl methacrylate copolymers | Proprietary* | 98 - 100 % | N              |

The substance(s) marked with a "Y" in the Hazard column above, are those identified as hazardous chemicals under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

\*The specific chemical identity is withheld because it is trade secret information of Arkema Inc.

While this material is not classified as hazardous under Federal OSHA regulations, this MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

**4. FIRST AID MEASURES**

**Inhalation:**

If inhaled, remove to fresh air.

**Skin:**

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse.

**Eyes:**

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

**Ingestion:**

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

**5. FIRE-FIGHTING MEASURES**

**Flash point** not applicable

**Auto-ignition temperature:** 860 °F (460 °C)

**Lower flammable limit (LFL):** not applicable

**Upper flammable limit (UFL):** not applicable

**Extinguishing media (suitable):**

Dry chemical, water spray, carbon dioxide, foam

**Protective equipment:**

## PLEXIGLAS® G-UVT ACRYLIC SHEET

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

**Further firefighting advice:**

Fire fighting equipment should be thoroughly decontaminated after use.

**Fire and explosion hazards:**

Heated material can form flammable vapors with air.

### 6. ACCIDENTAL RELEASE MEASURES

**In case of spill or leak:**

Pick up and transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

### 7. HANDLING AND STORAGE

**Handling**

**General information on handling:**

Avoid breathing processing fumes or vapors.

Avoid breathing dust.

Handle in accordance with good industrial hygiene and safety practices.

These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing.

**Storage**

**General information on storage conditions:**

Avoid extreme temperatures.

**Storage incompatibility – General:**

Store away from sources of heat and light.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Airborne Exposure Guidelines:**

**Engineering controls:**

Investigate engineering techniques to reduce exposures. Provide ventilation if necessary to minimize exposures. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

**Respiratory protection:**

Avoid breathing processing fumes or vapors. Avoid breathing dust. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where

## PLEXIGLAS® G-UVT ACRYLIC SHEET

there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

### Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

### Eye protection:

Processing of this product releases vapors or fumes which may cause eye irritation. Use good industrial practice to avoid eye contact. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                     |                |
|-------------------------------------|----------------|
| <b>Color:</b>                       | clear          |
| <b>Physical state:</b>              | solid          |
| <b>Form:</b>                        | sheets         |
| <b>Odor:</b>                        | odourless      |
| <b>pH:</b>                          | not applicable |
| <b>Density:</b>                     | not applicable |
| <b>Vapor pressure:</b>              | not applicable |
| <b>Vapor density:</b>               | not applicable |
| <b>Boiling point/boiling range:</b> | not applicable |
| <b>Freezing point:</b>              | not applicable |
| <b>Melting point/range:</b>         | not applicable |
| <b>Solubility in water:</b>         | insoluble      |
| <b>% Volatiles:</b>                 | 0 %            |

## PLEXIGLAS® G-UVT ACRYLIC SHEET

### 10. STABILITY AND REACTIVITY

**Stability:**

The product is stable under normal handling and storage conditions

**Hazardous reactions:**

Hazardous polymerization does not occur.

**Materials to avoid:**

None under normal conditions of use.

**Conditions / hazards to avoid:**

Avoid flames, welding arcs, potential ignition sources, or other high temperature sources which induce thermal decomposition.

**Hazardous decomposition products:**

Thermal decomposition may yield acrylic monomers. Thermal decomposition begins to generate monomer vapor at >570F (>300 C).

### 11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

**Data for Polymethyl methacrylate copolymers (Proprietary)**

**Acute toxicity**

**Oral:**

Practically nontoxic. (rat) LD50 = 8,000 mg/kg. (similar material)

**Genotoxicity**

**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, human cells

**Genotoxicity**

**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: animals

**Other information**

Biocompatibility testing for this polymer or its extracts has generally shown that the material is inert.

**Human experience**

**Skin contact:**

Skin: Irritant but not a sensitizer. Mechanical irritation. (studied using human volunteers)

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

**12. ECOLOGICAL INFORMATION**

**Chemical Fate and Pathway**

No data are available.

**Ecotoxicology**

No data are available.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal:**

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

**14. TRANSPORT INFORMATION**

**US Department of Transportation (DOT):** not regulated

**International Maritime Dangerous Goods Code (IMDG):** not regulated

**15. REGULATORY INFORMATION**

**Chemical Inventory Status**

|   |            |   |
|---|------------|---|
| EU. EINECS  | EINECS     | Does not conform  |
| US. Toxic Substances Control Act  | TSCA       | The components of this product are all on the TSCA Inventory. |
| Australia. Industrial Chemical (Notification and Assessment) Act  | AICS       | Conforms to   |
| Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) | DSL        | All components of this product are on the Canadian DSL list.  |
| Japan. Kashin-Hou Law List  | ENCS (JP)  | Conforms to   |
| Korea. Toxic Chemical Control Law (TCCL) List   | KECI (KR)  | Conforms to   |
| Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act                                       | PICCS (PH) | Conforms to   |
| China. Inventory of Existing Chemical Substances  | INV (CN)   | Conforms to   |

## PLEXIGLAS® G-UVT ACRYLIC SHEET

---

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand      NZIOC      Conforms to

### **United States – Federal Regulations**

#### **SARA Title III – Section 302 Extremely Hazardous Chemicals:**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA Title III - Section 311/312 Hazard Categories:**

No SARA Hazards

#### **SARA Title III – Section 313 Toxic Chemicals:**

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):**

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

#### **OSHA Regulated Carcinogens (NTP, IARC, OSHA Listed):**

##### **NTP:**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

##### **IARC:**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### **OSHA:**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

### **United States – State Regulations**

#### **Massachusetts Right to Know**

No components are subject to the Massachusetts Right to Know Act.

#### **New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

#### **Pennsylvania Right to Know**

|                                    |                |
|------------------------------------|----------------|
| <u>Chemical Name</u>               | <u>CAS-No.</u> |
| Polymethyl methacrylate copolymers | Proprietary    |

## PLEXIGLAS® G-UVT ACRYLIC SHEET

---

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

### 16. OTHER INFORMATION

---

#### Latest Revision(s):

|                   |             |
|-------------------|-------------|
| Reference number: | 00000058889 |
| Date of Revision: | 08/22/2008  |
| Date Printed:     | 09/17/2008  |

PLEXIGLAS® is a registered trademark of Arkema Inc.

ALTUGLAS® is a registered trademark of Arkema Inc.

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.