

PLEXIGLAS® SHEET: Sterilization

ACRYLIC SHEET

Ethylene Oxide Sterilization

All grades of PLEXIGLAS® sheet can be sterilized using ethylene oxide gas.

The statements, technical information and recommendations obtained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Altuglas International/Arkema expressly disclaims any and all liability. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OR MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.

The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein should be construed as an inducement to infringe any patent, and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See MSDS for Health & Safety Considerations. PLEXIGLAS® is a registered trademark of Arkema in the Americas. ©2013 Arkema Inc. All rights reserved. Rev. 5/13

800 523-7500

ALTUGLAS
INTERNATIONAL
ARKEMA GROUP

plexiglas.com

PLEXIGLAS®
BY ARKEMA