

PLEXIGLAS® G ACRYLIC SHEET COLORS**1. PRODUCT AND COMPANY IDENTIFICATION****Company**

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Altuglas International

Customer Service Telephone Number: (800) 523-1532
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)

Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: PLEXIGLAS® G ACRYLIC SHEET COLORS
Synonyms: Not available
Molecular formula: Mixture
Chemical family: Acrylic copolymers
Product use: Polymers industry, Special applications, in general

2. HAZARDS IDENTIFICATION**Emergency Overview**

Color: various colours
Physical state: solid
Form: sheets
Odor: odourless

***Classification of the substance or mixture:**
Not a hazardous substance or mixture.

GHS-Labeling

Supplemental Hazard Statements:
Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

Supplemental information:

Product code: A11700

Version 2.0

Issued on: 04/18/2018

Page: 1 / 13

PLEXIGLAS® G ACRYLIC SHEET COLORS

Potential Health Effects:

The product, in the form supplied, is not anticipated to produce significant adverse human health effects. Contains high molecular weight polymer(s). Effects due to processing releases: Irritating to eyes, respiratory system and skin.

Prolonged or repeated exposure may cause: drowsiness, nausea, headache, weakness, (severity of effects depends on extent of exposure).

Other:

Handle in accordance with good industrial hygiene and safety practice. (sheets) This product may release fume and/or vapor of variable composition depending on processing time and temperature. Hazardous decomposition products may include confirmed or suspected carcinogens. Secondary operations, such as grinding, sanding or sawing, can produce dust which may present a respiratory hazard.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Acrylic copolymer	Proprietary*	<= 100 %	Not classified
Methyl methacrylate	80-62-6	< 2 %	H225, H315, H317, H335

*The specific chemical identity is withheld because it is trade secret information of Arkema Inc.

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

PLEXIGLAS® G ACRYLIC SHEET COLORS

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of immediate medical attention and special treatment needed, if necessary:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

5. FIREFIGHTING MEASURES**Extinguishing media (suitable):**

Water spray, Carbon dioxide (CO₂), Foam, Dry chemical

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Heated material can form flammable vapors with air.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Pick up and transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

PLEXIGLAS® G ACRYLIC SHEET COLORS

7. HANDLING AND STORAGE

Handling

General information on handling:

Avoid breathing dust.
 Avoid breathing processing fumes or vapors.
 Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

Storage

General information on storage conditions:

Avoid extreme temperatures. Keep in a dry, cool place.

Storage incompatibility – General:

Store away from sources of heat and light.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Particles Not Otherwise Specified / Nuisance Dust (Proprietary)

US. ACGIH Threshold Limit Values

Form:	Inhalable particles.
Time weighted average	10 mg/m ³
Form:	Respirable particles.
Time weighted average	3 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form:	Respirable fraction.
PEL:	5 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form:	Total dust
PEL:	15 mg/m ³

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Respirable fraction.
Time weighted average	15millions of particles per cubic foot of air

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Total dust
Time weighted average	50millions of particles per cubic foot of air

US. OSHA Table Z-3 (29 CFR 1910.1000)

PLEXIGLAS® G ACRYLIC SHEET COLORS

Form: Respirable fraction.
Time weighted average 5 mg/m³

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form: Total dust
Time weighted average 15 mg/m³

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Respiratory protection:

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

Eye protection:

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Product code: A11700

Version 2.0

Issued on: 04/18/2018

Page: 5 / 13

PLEXIGLAS® G ACRYLIC SHEET COLORS

Color:	various colours
Physical state:	solid
Form:	sheets
Odor:	odourless
Odor threshold:	No data available.
Flash point	Not applicable
Auto-ignition temperature:	579 °F (304 °C)
Lower flammable limit (LFL):	No data available.
Upper flammable limit (UFL):	No data available.
pH:	No data available.
Density:	No data available.
Specific Gravity (Relative density):	Not applicable
Vapor pressure:	No data available.
Vapor density:	No data available.
Boiling point/boiling range:	No data available.
Melting point/range:	No data available.
Freezing point:	No data available.
Evaporation rate:	No data available.
Solubility in water:	insoluble
Viscosity, dynamic:	No data available.
Oil/water partition coefficient:	No data available.
Thermal decomposition:	572 °F (300 °C)
Flammability:	See GHS Classification in Section 2

10. STABILITY AND REACTIVITY

PLEXIGLAS® G ACRYLIC SHEET COLORS**Stability:**

The product is stable under normal handling and storage conditions and typical use temperatures.

Hazardous reactions:

None known.

Materials to avoid:

None under normal conditions of use.

Conditions / hazards to avoid:

Avoid flames, welding arcs, potential ignition sources, or other high temperature sources which induce thermal decomposition.

Hazardous decomposition products:

Thermal decomposition giving flammable and toxic products :

Carbon oxides

Acrylates

Methacrylates

Hazardous organic compounds

11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for PLEXIGLAS® G ACRYLIC SHEET COLORS**Acute toxicity****Inhalation:**

4 h Acute toxicity estimate > 40 mg/l.

Skin Sensitization:

Not a sensitizer. Buehler Test. (guinea pig) No skin allergy was observed

Data for Acrylic copolymer (Proprietary)**Acute toxicity****Oral:**

Practically nontoxic. (rat) LD50 = 8,000 mg/kg. (similar material)

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, human cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: animals

PLEXIGLAS® G ACRYLIC SHEET COLORS

Other information

Biocompatibility testing for this polymer or its extracts has generally shown that the material is inert. The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer:

Possible cross sensitization with other acrylates and methacrylates

Human experience**Skin contact:**

Skin: Irritant but not a sensitizer. Mechanical irritation. (studied using human volunteers)

Data for Methyl methacrylate (80-62-6)**Acute toxicity****Oral:**

Practically nontoxic. (rat) LD50 = 7,900 - 9,400 mg/kg.

Dermal:

Practically nontoxic. (rabbit) LD50 > 5,000 mg/kg.

Inhalation:

Practically nontoxic. (rat) 4 h LC50 = 30 mg/l. (vapor)

signs: respiratory irritation, breathing difficulties, anesthetic effects

Specific target organ toxicity - single exposure:

May cause respiratory irritation.

Skin Irritation:

Causes skin irritation. (rabbit)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

May cause allergic skin reaction. Guinea pig maximization test. Skin allergy was observed.

May cause allergic skin reaction. LLNA: Local Lymph Node Assay. (mouse) Skin allergy was observed.

Possible cross sensitization with other acrylates and methacrylates

Repeated dose toxicity

Chronic inhalation administration to rat and hamster / affected organ(s): olfactory tissue

Subchronic inhalation administration to rat and mouse / affected organ(s): bone marrow, kidney, liver, nasal tissues, respiratory tract, central nervous system, peripheral nervous system, olfactory tissue / signs: decreased survival / (Repeated exposure at high concentrations)

Repeated oral administration to rat / affected organ(s): kidney, Stomach, nervous system

Chronic drinking water administration to rat / affected organ(s): kidney / signs: increased organ weight

PLEXIGLAS® G ACRYLIC SHEET COLORS

Repeated dermal application administration to rat, rabbit / signs: irritation

Carcinogenicity

Chronic inhalation administration to rat and mouse / affected organ(s): lung, upper respiratory tract / signs: fibrosis, nasal lesions affecting the sense of smell / No increase in tumor incidence was reported. (increased mortality)

Chronic drinking water administration to rat / No increase in tumor incidence was reported.

Repeated dermal administration to rat / affected organ(s): skin / No increase in tumor incidence was reported.

Repeated dietary administration to dog / No increase in tumor incidence was reported.

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria

Both positive and negative responses for genetic changes were observed in laboratory tests using: animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: mice, rats

Developmental toxicity

Exposure during pregnancy. Inhalation (rat and mouse) / No birth defects were observed. (delays in development, levels produced toxic effects in the mothers and offspring)

Exposure during pregnancy. Oral (rabbit) / No birth defects were observed.

Reproductive effects

Reproduction Test. Inhalation (mouse) / No toxicity to reproduction

Reproduction Test. Oral (rat) / No toxicity to reproduction

Human experience**General:**

Epidemiology studies have not shown an increase in cancer .

Human experience**Inhalation:**

Respiratory system: irritation, asthma-like symptoms. (based on reports of occupational exposure to workers)

Dust and/or vapor are reported to cause irritation when proper industrial hygiene controls/procedures are not used.

Human experience**Skin contact:**

Skin: dermatitis, numbness, tingling, peripheral neuropathy. Skin allergy was observed. (based on reports of occupational exposure to workers)

PLEXIGLAS® G ACRYLIC SHEET COLORS**Human experience****Eye contact:**

Eyes: Lachrymation, irritation. (based on reports of occupational exposure to workers)

12. ECOLOGICAL INFORMATION**Chemical Fate and Pathway**

Data on this material and/or its components are summarized below.

Data for Methyl methacrylate (80-62-6)**Biodegradation:**

Readily biodegradable. (14 d) biodegradation 94 %

Octanol Water Partition Coefficient:

log Pow: = 1.38

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for Methyl methacrylate (80-62-6)**Aquatic toxicity data:**Practically nontoxic. *Lepomis macrochirus* (Bluegill sunfish) 96 h LC50 = 191 - 283 mg/lNo effect up to the limit of solubility. *Oncorhynchus mykiss* (rainbow trout) 96 h LC50 > 79 mg/l**Aquatic invertebrates:**Harmful. *Daphnia magna* (Water flea) 48 h EC50 = 69 mg/l**Algae:**Practically nontoxic. *Pseudokirchneriella subcapitata* (green algae) 72 h ErC50 > 110 mg/l**Microorganisms:**

Activated sludge 14 d EC50 > 100 mg/l

Chronic toxicity to fish:Practically nontoxic. *Danio rerio* (zebra fish) 35 d NOEC (Early-life Stage) = 9.4 mg/l**Chronic toxicity to aquatic invertebrates:**Practically nontoxic. *Daphnia magna* (Water flea) 21 d NOEC = 37 mg/l**13. DISPOSAL CONSIDERATIONS****Waste disposal:**

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

PLEXIGLAS® G ACRYLIC SHEET COLORS

14. TRANSPORT INFORMATION

US Department of Transportation (DOT): not regulated

International Maritime Dangerous Goods Code (IMDG): not regulated

15. REGULATORY INFORMATION

Chemical Inventory Status

US. Toxic Substances Control Act

TSCA

The components of this product are all on the TSCA Inventory.

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

No SARA Hazards

SARA Title III – Section 313 Toxic Chemicals:

The following components are subject to reporting levels established by SARA Title III, Section 313:

<u>Chemical name</u>	<u>CAS-No.</u>	<u>De minimis concentration</u>	<u>Reportable threshold:</u>
Methyl methacrylate	80-62-6	1.0 %	25000 lbs (Manufacturing and processing) 10000 lbs (Otherwise used (non-manufacturing/processing))

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

<u>Chemical name</u>	<u>CAS-No.</u>	<u>Reportable quantity</u>
Methyl methacrylate	80-62-6	1000 lbs

United States – State Regulations

New Jersey Right to Know

<u>Chemical name</u>	<u>CAS-No.</u>
Methyl methacrylate	80-62-6

PLEXIGLAS® G ACRYLIC SHEET COLORS

New Jersey Right to Know – Special Health Hazard Substance(s)

<u>Chemical name</u>	<u>CAS-No.</u>
Methyl methacrylate	80-62-6

Pennsylvania Right to Know

<u>Chemical name</u>	<u>CAS-No.</u>
Acrylic copolymer	Proprietary
Methyl methacrylate	80-62-6

Pennsylvania Right to Know – Environmentally Hazardous Substance(s)

<u>Chemical name</u>	<u>CAS-No.</u>
Methyl methacrylate	80-62-6

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

<u>Chemical name</u>	<u>CAS-No.</u>
1,4-Dioxane	123-91-1
Oxirane	75-21-8
Formaldehyde	50-00-0
Acetaldehyde	75-07-0

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

<u>Chemical name</u>	<u>CAS-No.</u>
Oxirane	75-21-8

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

PLEXIGLAS® G ACRYLIC SHEET COLORS

Latest Revision(s):

Reference number: 600002670
Date of Revision: 04/18/2018
Date Printed: 05/18/2018

ALTUGLAS® is a registered trademark of Arkema Inc.
PLEXIGLAS® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.

