

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Company**

Arkema Inc.  
900 First Avenue  
King of Prussia, Pennsylvania 19406

**Altuglas International**

**Customer Service Telephone Number:** (800) 523-1532  
(Monday through Friday, 8:00 AM to 5:00 PM EST)

**Emergency Information**

**Transportation:** CHEMTREC: (800) 424-9300  
(24 hrs., 7 days a week)  
**Medical:** Rocky Mountain Poison Center: (866) 767-5089  
(24 hrs., 7 days a week)

**Product Information**

**Product name:** PLEXIGLAS® G-UVT ACRYLIC SHEET  
**Synonyms:** Not available  
**Molecular formula:** Mixture  
**Chemical family:** Acrylic copolymers  
**Product use:** Polymers industry, Special applications, in general

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

**Color:** clear  
**Physical state:** solid  
**Form:** sheets  
**Odor:** odourless

**\*Classification of the substance or mixture:**  
Not a hazardous substance or mixture.

**GHS-Labeling**

**Supplemental Hazard Statements:**

Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

**Supplemental information:**

**Potential Health Effects:**

The product, in the form supplied, is not anticipated to produce significant adverse human health effects.  
Contains high molecular weight polymer(s). Effects due to processing releases or residual monomer: Irritating to eyes, respiratory system and skin.  
Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

depends on extent of exposure).

**Other:**

Handle in accordance with good industrial hygiene and safety practice. (sheets) Secondary operations, such as grinding, sanding or sawing, can produce dust which may present a respiratory hazard. This product may release fume and/or vapor of variable composition depending on processing time and temperature.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Acrylic copolymer	Proprietary*	>= 98 - <= 100 %	Not classified

\*The specific chemical identity is withheld because it is trade secret information of Arkema Inc.

\*\*For the full text of the H-Statements mentioned in this Section, see Section 16.

**4. FIRST AID MEASURES**

**Inhalation:**

If inhaled, remove victim to fresh air.

**Skin:**

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse.

**Eyes:**

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

**Ingestion:**

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

**5. FIREFIGHTING MEASURES**

**Extinguishing media (suitable):**

Water spray, Carbon dioxide (CO2), Foam, Dry chemical

**Protective equipment:**

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

**Further firefighting advice:**

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

Fire fighting equipment should be thoroughly decontaminated after use.

**Fire and explosion hazards:**

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

**6. ACCIDENTAL RELEASE MEASURES**

**In case of spill or leak:**

Pick up and transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

**7. HANDLING AND STORAGE**

**Handling**

**General information on handling:**

Avoid breathing dust.

Avoid breathing processing fumes or vapors.

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

**Storage**

**General information on storage conditions:**

Avoid extreme temperatures. Keep in a dry, cool place.

**Storage incompatibility – General:**

Store away from sources of heat and light.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Airborne Exposure Guidelines:**

**Particles Not Otherwise Specified / Nuisance Dust (Proprietary)**

US. ACGIH Threshold Limit Values

<b>Form:</b>	Inhalable particles.
Time weighted average	10 mg/m <sup>3</sup>
<b>Form:</b>	Respirable particles.
Time weighted average	3 mg/m <sup>3</sup>

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

<b>Form:</b>	Respirable fraction.
PEL:	5 mg/m <sup>3</sup>

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

---

**Form:** Total dust  
**PEL:** 15 mg/m3

US. OSHA Table Z-3 (29 CFR 1910.1000)

**Form:** Respirable fraction.  
Time weighted average 15millions of particles per cubic foot of air

**Form:** Total dust  
Time weighted average 50millions of particles per cubic foot of air

**Form:** Respirable fraction.  
Time weighted average 5 mg/m3

**Form:** Total dust  
Time weighted average 15 mg/m3

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

**Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

**Respiratory protection:**

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

**Skin protection:**

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

---

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

**Eye protection:**

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

<b>9. PHYSICAL AND CHEMICAL PROPERTIES</b>
--

<b>Color:</b>	clear
<b>Physical state:</b>	solid
<b>Form:</b>	sheets
<b>Odor:</b>	odourless
<b>Odor threshold:</b>	No data available
<b>Flash point</b>	Not applicable
<b>Auto-ignition temperature:</b>	860 °F (460 °C)
<b>Lower flammable limit (LFL):</b>	Not applicable
<b>Upper flammable limit (UFL):</b>	Not applicable
<b>pH:</b>	Not applicable
<b>Density:</b>	Not applicable
<b>Vapor pressure:</b>	Not applicable
<b>Vapor density:</b>	Not applicable
<b>Evaporation rate:</b>	No data available
<b>Solubility in water:</b>	insoluble
<b>% Volatiles:</b>	0 %
<b>Oil/water partition coefficient:</b>	No data available
<b>Thermal decomposition</b>	> 572 °F (> 300 °C)
<b>Flammability:</b>	See GHS Classification in Section 2

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

**10. STABILITY AND REACTIVITY**

**Stability:**

The product is stable under normal handling and storage conditions.

**Materials to avoid:**

None under normal conditions of use.

**Conditions / hazards to avoid:**

Avoid flames, welding arcs, potential ignition sources, or other high temperature sources which induce thermal decomposition.

**Hazardous decomposition products:**

Thermal decomposition giving flammable and toxic products:

Carbon oxides

Acrylates

Methacrylates

Hazardous organic compounds

**11. TOXICOLOGICAL INFORMATION**

Data on this material and/or a similar material are summarized below.

**Data for Acrylic copolymer (Proprietary)**

**Acute toxicity**

**Oral:**

Practically nontoxic. (Rat) LD50 = 8,000 mg/kg. (similar material)

**Genotoxicity**

**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, human cells

**Genotoxicity**

**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: animals

**Other information**

Biocompatibility testing for this polymer or its extracts has generally shown that the material is inert.

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer:

Possible cross sensitization with other acrylates and methacrylates

**Human experience**

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

**Skin contact:**

Skin: Irritant but not a sensitizer. Mechanical irritation. (studied using human volunteers)

**12. ECOLOGICAL INFORMATION**

**Chemical Fate and Pathway**

No data are available.

**Ecotoxicology**

No data are available.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal:**

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

**14. TRANSPORT INFORMATION**

**US Department of Transportation (DOT):** not regulated

**International Maritime Dangerous Goods Code (IMDG):** not regulated

**15. REGULATORY INFORMATION**

**Chemical Inventory Status**

EU. EINECS	EINECS	Conforms to
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Conforms to
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Conforms to
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to

**PLEXIGLAS® G-UVT ACRYLIC SHEET**

Philippines Inventory of Chemicals and Chemical Substances (PICCS) PICCS (PH) Conforms to

Australia Inventory of Chemical Substances (AICS) AICS Conforms to

**United States – Federal Regulations**

**SARA Title III – Section 302 Extremely Hazardous Chemicals:**

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

**SARA Title III - Section 311/312 Hazard Categories:**

No SARA Hazards

**SARA Title III – Section 313 Toxic Chemicals:**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):**

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

**United States – State Regulations**

**New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

**Pennsylvania Right to Know**

<u>Chemical Name</u>	<u>CAS-No.</u>
Acrylic copolymer	Proprietary

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

**16. OTHER INFORMATION**

**Latest Revision(s):**

Reference number:	000000058889
Date of Revision:	05/28/2015
Date Printed:	05/28/2015

ALTUGLAS® is a registered trademark of Arkema Inc.  
PLEXIGLAS® is a registered trademark of Arkema Inc.



**PLEXIGLAS® G-UVT ACRYLIC SHEET**

---

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.