

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET****1. PRODUCT AND COMPANY IDENTIFICATION****Company**

Arkema Inc.  
900 First Avenue  
King of Prussia, Pennsylvania 19406

**Altuglas International**

**Customer Service Telephone Number:** (800) 523-1532  
(Monday through Friday, 8:00 AM to 5:00 PM EST)

**Emergency Information**

**Transportation:** CHEMTREC: (800) 424-9300  
(24 hrs., 7 days a week)

**Medical:** Rocky Mountain Poison Center: (866) 767-5089  
(24 hrs., 7 days a week)

**Product Information**

**Product name:** PLEXIGLAS® SB COLORLESS ACRYLIC SHEET  
**Synonyms:** Not available  
**Molecular formula:** Mixture  
**Chemical family:** Acrylic copolymers  
**Product use:** Polymers industry, Special applications, in general

**2. HAZARDS IDENTIFICATION****Emergency Overview**

**Color:** colourless  
**Physical state:** solid  
**Form:** sheets  
**Odor:** odourless

**\*Classification of the substance or mixture:**  
Not a hazardous substance or mixture.

**GHS-Labeling****Supplemental Hazard Statements:**

Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 1 / 10

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

**Supplemental information:**

**Potential Health Effects:**

The product, in the form supplied, is not anticipated to produce significant adverse human health effects. Contains high molecular weight polymer(s). Effects due to processing releases or residual monomer: Irritating to eyes, respiratory system and skin. Possible cross sensitization with other acrylates and methacrylates. Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure).

**Other:**

Handle in accordance with good industrial hygiene and safety practice. (sheets) Secondary operations, such as grinding, sanding or sawing, can produce dust which may present a respiratory hazard. This product may release fume and/or vapor of variable composition depending on processing time and temperature.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Acrylic copolymer	Proprietary*	<= 100 %	Not classified

\*The specific chemical identity is withheld because it is trade secret information of Arkema Inc.

\*\*For the full text of the H-Statements mentioned in this Section, see Section 16.

**4. FIRST AID MEASURES**

**4.1. Description of necessary first-aid measures:**

**Inhalation:**

If inhaled, remove victim to fresh air.

**Skin:**

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eyes:**

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

**Ingestion:**

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 2 / 10

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

**4.2. Most important symptoms/effects, acute and delayed:**

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information if applicable) and Section 11 (Toxicology Information) of this SDS.

**4.3. Indication of immediate medical attention and special treatment needed, if necessary:**

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

**5. FIREFIGHTING MEASURES****Extinguishing media (suitable):**

Water spray, Carbon dioxide (CO<sub>2</sub>), Foam, Dry chemical

**Protective equipment:**

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

**Further firefighting advice:**

Fire fighting equipment should be thoroughly decontaminated after use.

**Fire and explosion hazards:**

Heated material can form flammable vapors with air.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Pick up and transfer to properly labelled containers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

**Protective equipment:**

Appropriate personal protective equipment is set forth in Section 8.

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

**7. HANDLING AND STORAGE**

**Handling**

**General information on handling:**

Avoid breathing dust.  
 Avoid breathing processing fumes or vapors.  
 Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

**Storage**

**General information on storage conditions:**

Avoid extreme temperatures. Keep in a dry, cool place.

**Storage incompatibility – General:**

Store away from sources of heat and light.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Airborne Exposure Guidelines:**

**Particles Not Otherwise Specified / Nuisance Dust (Proprietary)**

US. ACGIH Threshold Limit Values

Form:	Respirable particles.
Time weighted average	3 mg/m <sup>3</sup>
Form:	Inhalable particles.
Time weighted average	10 mg/m <sup>3</sup>

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Respirable fraction.
Time weighted average	15millions of particles per cubic foot of air

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Total dust
Time weighted average	50millions of particles per cubic foot of air

US. OSHA Table Z-3 (29 CFR 1910.1000)

Form:	Respirable fraction.
Time weighted average	5 mg/m <sup>3</sup>

US. OSHA Table Z-3 (29 CFR 1910.1000)

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

Form:	Total dust
Time weighted average	15 mg/m3

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

**Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

**Respiratory protection:**

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

**Skin protection:**

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

**Eye protection:**

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Color:</b>	colourless
<b>Physical state:</b>	solid
<b>Form:</b>	sheets
<b>Odor:</b>	odourless

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 5 / 10

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

---

<b>Odor threshold:</b>	No data available
<b>Flash point</b>	Not applicable
<b>Auto-ignition temperature:</b>	860 °F (460 °C)
<b>Lower flammable limit (LFL):</b>	Not applicable
<b>Upper flammable limit (UFL):</b>	Not applicable
<b>pH:</b>	Not applicable
<b>Density:</b>	Not applicable
<b>Specific Gravity (Relative density):</b>	No data available
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Boiling point/boiling range:</b>	No data available
<b>Melting point/range:</b>	No data available
<b>Freezing point:</b>	No data available
<b>Evaporation rate:</b>	No data available
<b>Solubility in water:</b>	insoluble
<b>Viscosity, dynamic:</b>	No data available
<b>% Volatiles:</b>	0 %
<b>Oil/water partition coefficient:</b>	No data available.
<b>Thermal decomposition:</b>	> 572 °F (> 300 °C)
<b>Flammability:</b>	See GHS Classification in Section 2 if applicable

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

---

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 6 / 10

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET****Stability:**

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

**Hazardous reactions:**

None known.

**Materials to avoid:**

None under normal conditions of use.

**Conditions / hazards to avoid:**

Avoid flames, welding arcs, potential ignition sources, or other high temperature sources which induce thermal decomposition.

**Hazardous decomposition products:**

Thermal decomposition giving flammable and toxic products :

Carbon oxides

Acrylates

Methacrylates

Hazardous organic compounds

**11. TOXICOLOGICAL INFORMATION**

Data on this material and/or its components are summarized below.

**Data for Acrylic copolymer (Proprietary)****Other information**

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance. Effects due to processing releases or residual monomer:  
Possible cross sensitization with other acrylates and methacrylates

**12. ECOLOGICAL INFORMATION****Chemical Fate and Pathway**

No data are available.

**Ecotoxicology**

No data are available.

**13. DISPOSAL CONSIDERATIONS****Waste disposal:**

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 7 / 10

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

**14. TRANSPORT INFORMATION**

**US Department of Transportation (DOT):** not regulated

**International Maritime Dangerous Goods Code (IMDG):** not regulated

**15. REGULATORY INFORMATION**

**Chemical Inventory Status**

US. Toxic Substances Control Act	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Does not conform
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

**United States – Federal Regulations**

**SARA Title III – Section 302 Extremely Hazardous Chemicals:**

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

**SARA Title III - Section 311/312 Hazard Categories:**

No SARA Hazards

**SARA Title III – Section 313 Toxic Chemicals:**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 8 / 10



**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

**Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):**

<u>Chemical name</u>	<u>CAS-No.</u>	<u>Reportable quantity</u>
Methyl methacrylate	80-62-6	1000 lbs

**United States – State Regulations**

**New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

**Pennsylvania Right to Know**

<u>Chemical name</u>	<u>CAS-No.</u>
Acrylic copolymer	Proprietary
Methyl methacrylate	80-62-6

**Pennsylvania Right to Know – Environmentally Hazardous Substance(s)**

<u>Chemical name</u>	<u>CAS-No.</u>
Methyl methacrylate	80-62-6

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

**16. OTHER INFORMATION**

Latest Revision(s):  
 Reference number: 600001923  
 Date of Revision: 12/08/2020  
 Date Printed: 12/09/2020

PLEXIGLAS® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be

**PLEXIGLAS® SB COLORLESS ACRYLIC SHEET**

---

construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

*Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.*

*It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.*

---

Product code: 11744

Version 1.0

Issued on: 12/08/2020

Page: 10 / 10